

Storage & Installation Instructions

Storage:

AnchorDeck™ PSU should be sheltered from the elements, stored at room temperature, upright in a dry and properly ventilated location. Keep AnchorDeck™ PSU away from all flames, sparks and volatile substances.

Installation Instructions:

For slopes 2:12 and greater

Install AnchorDeck™ PSU horizontally (parallel) to the eave using 3" horizontal laps and 6" vertical laps as per **Diagram A** on page 2.

For slopes ½:12 to 2:12

Install AnchorDeck™ PSU horizontally (parallel) to the eave using 18" horizontal laps and 6" vertical laps as per **Diagram B** on page 2.

Required modification for installation under metal roof systems with slopes ½:12 to 2:12

Vertical end laps must be a minimum of 6 inches wide and 3 feet apart from the course above and below. ASTM D4586 compliant roof cement should be applied 6 inches wide at all underlying vertical end laps with the overlying vertical end lap set into the roof cement. Apply firm pressure over the entire vertical end lap with a weighted roller.

Optimal results are achieved when Installed in temperatures over 40°F (4.4°C). For temperatures below 40°F (4.4°C) a primer and 3/8" head roofing nails should be used in the overlap area.

Start installation from the lowest point to the highest point of the roof. Apply AnchorDeck™ PSU in valleys before applying it to the eaves.

For maximum ice dam protection, we recommend installing AnchorDeck™ PSU 24" (minimum) past the interior wall from the eave. Consult your local building code/authority for specific regional requirements.

Repair all holes, including fasteners that have been

removed, damage and tears to the membrane with a round patch of membrane extending past the damaged area by 6" in all directions.

For high wind or wind-driven rain protection it is recommended to cover the entire roof deck.

Apply firm pressure with a weighted roller over all laps for optimal sealing.

For best results, final roof covering should be applied as soon as possible. AnchorDeck™ PSU is not designed for exposure longer than 90 days.

Safety:

Roofers should make sure to always follow safe roofing practices and OSHA safety requirements. Roofers should always use and wear fall protection devices when working on roofs. Some of the examples are toe boards, rope, harnesses and rubber-soled footwear. Safety glasses should always be worn when cutting the roof with a power tool. Wear gloves when installing to avoid cuts and abrasions.

Use caution when walking or standing on AnchorDeck™ PSU in wet, icy and/or dusty conditions that may reduce traction. Failure to use proper safety gear and footwear can result in serious injury.



Got Metal?

AnchorDeck™ PSU can handle the heat!

AnchorDeck™ PSU is the ideal self-adhered underlayment for use under stone coated steel shingles, all metal panels and metal accents.

**-40° F to 240° F
temperature range**




*See our website for full T&C's

Sentry Building Innovations
1209 Orange Street, Wilmington,
New Castle, Delaware 19801
Customer Service: 1-843-735-1773



**AnchorDeck™ PSU application
for slopes 2:12 or greater**



**AnchorDeck™ PSU application
for slopes ½:12 to 2:12**

