



## ALL-WEATHER PROTECTION



**NEXGEN**  
SYNTHETICS

### Roofnado™ AnchorDeck™

AnchorDeck™ is a next generation synthetic roofing underlayment for sloped roof applications. AnchorDeck™ coating technology allows underlayment to be anchored to the deck prior to applying fasteners. Innovative high-traction walking surface, excellent durability and many other unique performance features make AnchorDeck™ the smart choice for today's roofing professionals.

AnchorDeck™ is designed for use under asphalt shingles, metal panels and shingles, synthetic shingles and primed cedar shakes. AnchorDeck™ meets all the code requirements including ASTM D226, ASTM D4869 and AC 188 as required by ICC-ES.

AnchorDeck™ not only protects your roof deck, it helps protect Roofers as well. Ask for it at your nearest roofing distributor today!


### Features & Benefits

- AnchorDeck™ has a unique coating technology which allows underlayment to be anchored to the deck prior to applying fasteners.
- All temp. all weather performance; remains flexible and easy to install in freezing or extremely hot conditions (-40° to 240° F)
- †No stretching around fasteners & no blow-offs!
- Innovative high traction walking surface
- Meets ASTM D226 Types I & II and D4869 Types II & IV
- Meets the performance requirements of CAN/CSA A123.3
- Miami-Dade County Product Control Approved
- ICC-ES ESR-4055 | FBC Approved – FL21895
- Class A Fire Rating - ASTM E108
- Texas Department of Insurance Approved
- 90 Days UV Exposure
- 20 year warranty

### Test/Standard\*

### Typical Value

Nominal thickness	11 mils
Tensile Strength ASTM D5034	MD 95 lbs (43 kg)   CD 85 lbs (38.5 kg)
Tear Strength ASTM D4533	MD 18 lbs (8.16 kg)   CD 16 lbs (7.26 kg)
Liquid Water Transmission ASTM D4869	Pass
Fire Rating ASTM E108	Class A
UV Exposure	3 Months
Temperature Range	-40° F - 240° F



**Steep slope confidence**

walkability you can trust – every time.

### Roll/Pallet Specs

Length per roll:	286' / 87 m
Width per roll:	42" / 1.1 m
Weight per roll:	23 lbs / 10.4 kg
Roll size:	10 sq / 93 m <sup>2</sup>
Rolls per pallet/truck:	49 / 1,960
Pallet weight:	1,177 lbs / 534 kg

\*Test data is based on average taken over several production runs and should not be considered or interpreted as minimum or maximum values. Values are typical data and not limiting specifications. All values ± 10 %. This product is manufactured in accordance with national standards which allow for non-critical variances in weights and measures.

†When correctly installed as per AnchorDeck™ installation instructions. All Roofnado™ product installation instructions are available to download or view from our website: [www.roofnado.com](http://www.roofnado.com) RN AD SS JAN23

**Switch to Roofnado™ and start saving on labor, time & money. Contact us today!**  
[www.roofnado.com](http://www.roofnado.com)

