ROOFNADO™ ShingleLock™

SNOW STORMS RAIN HAIL WIND UV

NEXGEN™ SYNTHETICS

ALL TEMP. ALL WEATHER PERFORMANCE

ShingleLock™ is an engineered synthetic roofing underlayment for sloped roof applications. It has a patented ShingleLock™ mechanical and chemical slip-resistant walking surface using advanced polymer technology which: provides superior steep-slope walkability, helps prevent shingle bundles from sliding, improves roofer safety, and increases productivity.

In addition, ShingleLock™ has a uniquely designed coating technology which allows the underlayment to be anchored to the deck prior to using fasteners. ShingleLock™ is designed for use under asphalt shingles, concrete tiles, all metal panels, synthetic shingles and primed cedar shakes. ShingleLock™ meets all the code requirements including ASTM D226, ASTM D4869 and AC 188 as required by ICC-ES. ShingleLock™ not only protects your roof deck, it helps protect roofers as well.

Ask for it at your nearest roofing distributor today.

- Patented ShingleLock™ technology which provides superior steep-slope walkability for roofers and helps prevent shingle bundles from sliding
- All temp. all weather performance; remains flexible and easy to install in freezing or extremely hot conditions (-40° to 212°F)
- †No stretching around fasteners & no blow-offs!
- Meets the performance requirements of CAN/CSA A220.1
- ICC-ES ESR-4055 | FBC Approved – FL21895
- Class A fire rating - ASTM E108
- Texas Department of Insurance Approved
- Meets ASTM D226 Types I & II and D4869 Types II & IV
- 180 days UV exposure
- High Definition (HD) printing
- Limited Lifetime Warranty

ICC ES ESR-4055

Lifetime
LIMITED WARRANTY

ROOFNADO™ ShingleLock™

Roofnado.com

Sentry Building Innovations

1209 Orange Street, Wilmington,

New Castle, Delaware 19801

Customer Service: 1-843-735-1773

Test/Standard*	Typical Value
Tensile Strength ASTM D5034	MD 140 lbs (63.5 kg) | CD 120 lbs (54.4 kg)
Tear Strength ASTM D4533	MD 40 lbs (18.1 kg) | CD 35 lbs (15.9 kg)
Liquid Water Transmission ASTM D4869	Pass
Fire Rating ASTM E108	Class A
UV Exposure	6 Months
Temperature Range	-40° - 212° F

Roll/Pallet Specs

Length per roll:	250′ / 76.2 m
Width per roll:	48″ / 1.2 m
Weight per roll:	39 lbs / 17.7 kg
Roll size:	10 sq / 93 m^2
Rolls per pallet/truck:	30 / 1080
Pallet weight:	1,220 lbs / 553 kg

*Test data is based on average taken over several production runs and should not be considered or interpreted as minimum or maximum values. Values are typical data and not limiting specifications. All values ± 10 %. This product is manufactured in accordance with national standards which allow for non-critical variances in weights and measures.

†When correctly installed as per ShingleLock™ installation instructions. All Roofnado™ product installation instructions are available to download or view from our website: www.roofnado.com

ENG-RN-SL-DIGITAL R8 NOV2019