



Roofnado™ LapLock™ PSU HT

LapLock™ PSU HT is a high temp. self adhered roofing underlayment for sloped roof applications. LapLock™ provides unmatched protection from storms, hail, ice-dams, wind-driven rain, snow and water. LapLock™ PSU HT has a mechanical slip resistant walking surface which provides superior steep slope walkability for roofers. In addition, LapLock's dual-locking lap technology creates an outstanding water-tight seal that keeps your roof dry no matter what Mother Nature throws at it.

LapLock™ PSU HT is designed for use under asphalt shingles, concrete tiles, all metal panels and shingles, shakes, synthetic shingles and primed cedar shakes. LapLock™ PSU HT meets all building code requirements including ASTM D226, ASTM D4869 and AC 48. Ask for it at your nearest roofing distributor today.

Features & Benefits

- Premium protection from Ice Dams, Snow Storms, Hail & Wind-Driven Water
- Mechanical slip resistant walking surface which provides superior steep slope walkability for roofers
- High temp. self adhered with a split release liner
- LapLock™ dual-locking technology for water tight seals on laps
- Meets the performance requirements of CAN/CSA A220.1
- Meets and exceeds ASTM D1970
- Polyfoam/ICP adhesive approved
- ICC-ES ESR-4054 | FBC Approved – FL21895
- Texas Department of Insurance Approved
- Low temperature flexibility: AC 48 PASS
- Limited Lifetime Warranty
- 180 days UV exposure
- Temperature range: 40° F to 240° F

Test/Standard*

Typical Value

Nominal thickness	50 mils
Weight per square	23 lbs
Permeability ASTM E96	0.027 Perms
Nail Sealability ASTM D1970	Pass
Tensile Strength ASTM D5034	MD 105 lbs (47.6 kg) CD 90 lbs (40.8 kg)
Tear Strength ASTM D4533	MD 35 lbs (15.8 kg) CD 30 lbs (13.6 kg)
Adhesion to Plywood ASTM D903	4 lbs/inch
Liquid Water Transmission ASTM D4869	Pass
Fire Rating ASTM E108	Class A
UV Exposure	6 Months



Roll/Pallet Specs

Length per roll:	67' / 20.4 m
Width per roll:	36" / 0.91 m
Weight per roll:	46.5 lbs / 21.1 kg
Roll size:	2 sq / 20 m ²
Rolls per pallet/truck:	25
Pallet weight:	1,230 lbs / 559 kg

*Test data is based on average taken over several production runs and should not be considered or interpreted as minimum or maximum values. Values are typical data and not limiting specifications. All values ± 10 %. This product is manufactured in accordance with national standards which allow for non-critical variances in weights and measures.

†When correctly installed as per installation instructions. All product installation instructions are available to download or view from our website: www.roofnado.com

AD PSU HT SS MAR24

Switch to Roofnado™ and start saving on labor, time & money. Contact us today!
www.roofnado.com

